

FV 250.2 – Pots and Pan washer.



- Wash and final rinse system incl. ascending pipes in stainless steel
- Aqua-stop system with bottom sheet leakage water control
- Drain filter system AktivPlus
- Airgap with booster pump
- Mike 2 control with infrared interface for easy exchange of service data
- Entry height 890 mm
- 3 programme cycles with temperature display for tank and final rinse water
- Reversing wash arms
- Convincing washing results
- Double-wall construction with additional insulation and rear cladding as a standard
- Rounded wash tank
- Drain pump as a standard
- Drain possible at any height up to 700 mm
- Wash pump with dish protecting soft start
- Wash tank completely covered with easily removable tank filter sieve

Technical Data

Dimensions

Width	1490 mm
Depth	895 mm
Height	1935 mm
Height with open door	2490 mm
Entry height	890 mm
Basket dimensions	1310 x 700 mm

Machine Weight

Net weight (empty)	374 kg
Operational (full with water/no crockery)	474 kg
Gross (with packaging)	430 kg

Capacities

Cycles*	120/240/480 sec
Capacity	30/15/7 baskets/h
Capacity (according to USA calculation)	42/21/10 baskets/h
Pump motor	2 x 2,2 kW
Tank content	85 ltr.
Final rinse	9 ltr./basket
Tank heating	9 kW

Built-in boiler

10°C inlet temperature	18 kW
45°-60°C inlet temperature	12 kW

Total connected load for three phase current 3NPE 400V-50Hz

10°C inlet temperature	22,73 kW
45°-60°C inlet temperature	16,73 kW

Type of protection

Type of protection	IPX5
--------------------	------

Drawing:

